

Maximum Flexibility is the hallmark of the **Nautilus Hyosung 7600T**. Options for safe door swing – left or right – address difficult installation challenges. Options for deposit processing technologies allow institutions to accommodate cardholder preferences. Security options foster peace of mind. And all are delivered in a functional, high-capacity device.



TRANSFORM YOUR BANK BRANCHES WITH BRANCHSERV

Market Strength Capabilities

The **7600T** offers end-to-end deposit automation, and supports a full range of personalization, advertising and marketing options via a 15.1" color TFT. As with all Nautilus Hyosung products, **7600T** modules are designed, engineered, manufactured and tested in-house with 24/7 unattended self-service functionality as the goal. Subsequently, the **7600T** is reliable as it is functional – with a migration path for institutions with a vision.

Security

The **7600T**'s UL291 Level 1 rated safe has been proven in the field time and again. Additional standard features like the safe door seam lip cover and an option to hinge the safe door on the left or right mean you need not sacrifice secu-

urity for convenience. Certified keyboards give you the ability to comply with PCI EPP requirements, and optional security cameras for both surveillance and cash withdrawal areas allow you to protect both your customers and your cash assets at the ATM. Optional software and transactional security features are available.

Dependability

The **7600T** is the ideal self-service platform for weather-facing exterior walk-up deployments due to the reliability that comes with the Nautilus Hyosung name, and the capacity provided by the machine's integrated modules.

The **Monimax 7600T** is designed with "customerization" in mind; offering the most deployment and feature/function options for equipment of its kind, in a highly secure platform.

System Control

- Microsoft® Windows 7® platform
- Intel® processor
- NDC+ user application

Customer Display

- 15" color TFT LCD
- Privacy filter (standard)
- Sunlight readable (standard)
- Touch screen

Communication

- TCP/IP
- Wireless x .25 capable

Input Type

- PCI EPP (encrypting PIN pad)
- ADA compliant

Supervisor Operation

- 15" TFT color LCD touch screen

Card Handling

- Dip-type card reader
- Anti-skimming (optional)

Cash Dispensing

- 3,000-notes cassettes up to four cassettes
- Bundle retraction
- Automatic shutter

Depository Options

- Bulk check acceptor
- Bulk note acceptor
- Envelope depository

Printers

- 3.1" graphical thermal receipt printer
- 5,000 transaction receipt printer
- Electronic journal

Security

- UL291 Level 1 Safe
- Electronic safe lock (standard)

- KABA Mas Cencon safe lock (optional)
- Security camera (optional)

Miscellaneous

- Lead-through indicator
- Heater (standard)

Power Supply

- AC 110-240V, 50-60 Hz
- Backup battery

Operating Environment

- Temperature: -31°F - 104°F
- Humidity: 25% - 85%

Dimensions

- Height: 69.3" (1,760mm)
- Width: 32.7" (831mm)
- Depth: 40.6" (1,032mm)
- Weight: 1,977.5lbs. (897kg)



Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

- 15" color customer display
- Sunlight-readable screen
- 3.1" graphic thermal receipt printer
- PCI EPP (encrypting PIN pad)
- Cash dispenser

- Optional security camera
- Bundle check acceptor
- Card reader
- Audio Jack
- Bundle note acceptor